

# DATA SHEET

## THE RUNPO – triple twisted, Ø 5,3 mm






### SPECIFICATION

(RRP/excl. of VAT)

LENGTH	20 m	30 m			
WEIGHT/KG	1,06 kg	1,30 kg			
ITEM NO.	10013	10014			
PRICE €	<b>€ 124,90</b>	<b>€ 139,90</b>			
ROD MATERIAL	triple twisted special polyester				
ROD Ø	5,3 mm				
BENDING RADIUS	15 mm				
TOTAL TENSION LOAD	270 kg (on the entire band!)				
TUBE Ø	optimal from 16 mm – 40 mm				

### Recommended tube diameter, bending radius and tension loads of the RUNPO (twisted, Ø 5,3 mm)

Ø			
5,3 mm	16–40 mm	15 mm	270 Kg

### DESCRIPTION

The RUNPO (twisted, Ø 5,3 mm) is a further innovation by RUNPOTEC and an absolute all-rounder. The main reason for the success of the RUNPO (twisted, Ø 5,3 mm) is the patented flexible starting head RUNPOGLIDER with swivel, with a bigger eyelet on top. It enables to go over narrow radii due to its excellent flexural and gliding behaviour. The whole system has an unbelievable breaking load of 270 kg, the friction resistance is 50 % less due to its punctual contact. The advantages compared to the 3 mm glassfiber fish tape are: No kinks, no sticking thereby, no more need to glue or repair anything, considerable saving of time. The RUNPO (twisted, Ø 5,3 mm) is almost unbreakable, stored in a compact storage box which is extremely impact resistant, available in lengths of 20 m and 30 m. Every RUNPO (twisted, Ø 5,3 mm) is provided with two pressed RUNPOGLIDER with swivel at the end and the beginning of fish tape.